

XL GRIP (BHL) - Teknik Özellikler



Description

XL GRIP (BHL) kazma, hafriyat ve yükleme uygulamalarındaki ağır yük gerektiren çalışmalarda kullanılan ters kepçe yükleyiciler için özel olarak tasarlanmıştır. Doğrusal olmayan diş deseni en iyi çekiş gücünü ve istikrarı sağlar. Özel diş bileşimi, kesilme ve parçalanmaya karşı kusursuz dayanıklılık ve daha uzun sırt ömrü sunar.

UM

US Standard

Construction

 BIAS

Machinery

Endüstriyel: Bekoloder

Version	INDUSTRIAL
Type	TT
Tyre Size	14.9 - 24
LI/SS	145 A8

Dimensions US Standard

Usa code	94045396
Ply Rating	12
Section Width (inch)	15
Overall Diameter (inch)	48.8
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	143.5
Rim Rec	DW 13
Rim Alt	DW 11 ; DW 12 ; DW 13L

Load capacity (lbs)

mph / psi	42
25	6400

Printed on 4/20/2024 6:56 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..