

XL GRIP (E3) - Teknik Özellikler



Description

XL GRIP (E-3) sıra dışı çekiş gücünün gerektiği ağır koşullarda kesilme ve delinmeleri en aza indirmek üzere tasarlanmış, sabit damperlere yönelik çapraz kuşaklı bir lastiktir. Bu özellikler daha uzun bir lastik ömrü sağlar.

UM

US Standard

Construction

 BIAS

Machinery

Yoldışı: Sabit kaya kamyonu

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94015771
Ply Rating	32
Overall Width (inch)	20.1
Overall Diameter (inch)	63.6
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	188.2
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	83	109
30	19300	-
5	-	33100

Printed on 4/20/2024 7:57 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..