

XL GRIP (G3) - Teknik Özellikler



Description

XL GRIP (G-3) sıra dışı çekiş gücünün gerektiği, ağır yüklerle çalışılan toprak düzeltme işlerinde kesilme ve delinmeleri en aza indirmek üzere tasarlanmış, greyderlere yönelik çapraz kuşaklı bir lastiktir.

UM

International Standard

Construction

 BIAS

Machinery

Yoldışı: Greyder

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	510
Overall Diameter (mm)	1615
Static Loaded Radius (mm)	739
Rolling Circumference (mm)	4780
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	G3

Load capacity (Kg)

km/h / bar	5.75
40	9015

Printed on 4/27/2024 10:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..