

## XL GRIP IND3 (RTG) - Teknik Özellikler



### Description

XL GRIP (IND-3), istifleme ve kaldırma uygulamalarında RTG vinçlerine yönelik çapraz katlı bir lastiktir. Lastik, özel olarak formüle edilmiş bir sırt hamurundan yapılmış, daha uzun bir lastik ömrü sağlayan güçlü bir gövdeye sahiptir.

### UM

US Standard

### Construction

BIAS

### Machinery

Endüstriyel: RTG Vinç

Version	INDUSTRIAL
Type	TL
Tyre Size	21.00 - 25

## Dimensions US Standard

Usa code	94027316
Ply Rating	32
Overall Width (inch)	22.7
Overall Diameter (inch)	68.9
Static Loaded Radius (inch)	31.1
Rolling Circumference (inch)	204.1
Rim Rec	15.00/3.0
Rim Alt	17.00/3.0
TRA Code	IND3

## Load capacity (lbs)

mph / psi	113
5	52900

Printed on 5/6/2024 8:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..