

## XL GRIP (T) - Teknik Özellikler



### Description

XL GRIP (E-3) özellikle madencilik uygulamalarında ağır yükler taşıyan yol ve araziye yönelik kamyonlar için uygundur. Diş bileşiği en sert zemin koşullarında kesilme ve delinmeleri en aza indirmek üzere tasarlanmıştır. XL GRIP (E-3) sıra dışı çekiş gücü ve daha uzun lastik ömrü sunar.

### UM

International Standard

### Construction

BIAS

### Machinery

Yoldışı: Yol ve yol dışı kamyon

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

## Dimensions International Standard

Ply Rating	20
Overall Width (mm)	320
Overall Diameter (mm)	1250
Static Loaded Radius (mm)	585
Rolling Circumference (mm)	3710
Rim Rec	8.5
Rim Alt	8.0

## Load capacity (Kg)

km/h / bar	7.90
80 LS/LD	3875

Printed on 4/11/2024 2:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..