



## ***AGRIMAX RI 818 - Data Sheet***



*Description*

AGRIMAX RI 818 is a radial tire, which has been specifically developed for irrigation applications with pivot irrigators. Its specially designed tread pattern provides excellent traction in wet and muddy conditions in addition to outstanding self-cleaning properties.

*UM*

International Standard

*Construction*

RADIAL

*Machinery*

Agriculture: Pivot Irrigator

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
280/85 R 24 (11.2 R 24)	STANDARD	140	W 10	W 9	287	1086	490	3271	TL
320/85 R 38 (12.4 R 38)	STANDARD	154	W 10	W 9 ; W 11	319	1509	691	4565	TL

Printed on 22/09/2021 07:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..