

AGRIMAX SIRIO - Technical Specifications



Description

AGRIMAX SIRIO is a high-speed tire (up to 70 km/h - 45 mph) developed by BKT for high-performance tractors. Its design is perfect for both haulage and soil tillage applications. The high sidewall flexibility ensures outstanding stability, handling and comfort to improve the driving experience. It is also available with IF technology that allows to carry heavy loads at a low inflating pressure. The reinforced casing and the high number of belts guarantee great traction on the field whereas the low rolling resistance contributes to better fuel economy.

UM

US Standard

Construction

RADIAL

Machinery

Agriculture: High-Power Tractor

Version	HIGH SPEED
Type	TL
Tyre Size	710/70 R 38
LI/SS	171 D/168 E

Dimensions US Standard

Usa code	94044283
Section Width (inch)	28.2
Overall Diameter (inch)	77.1
Static Loaded Radius (inch)	34.9
Rolling Circumference (inch)	229.9
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E4-106R-000818
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	5810	6670	7660	8640	9630	10630	11490	12350
40	6380	7330	8410	9490	10580	11660	12610	13560
30	6700	7690	8840	9980	11110	12260	13250	14240
25	6990	8020	9210	10390	11580	12780	13810	14850
15	7560	8690	9960	11250	12540	13820	14950	16070
5	9570	10990	12610	14240	15870	17490	18910	20340

Printed on 03/12/2021 06:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..