

AT 621 - Technical Specifications



Description

AT 621 is suitable for backhoe loaders and compact loaders in all digging and loading operations in agriculture. The AT 621 tire features an extra deep tread which ensures great cut and chip resistance and higher durability. In addition, this BKT tire ensures great durability and self cleaning properties. AT 621 is available in several versions to meet the most differing user requirements.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Compact Loader, Backhoe Loader
Industrial: Backhoe Loader, Compact Loader

Version	STANDARD
Type	TT
Tyre Size	33 X 12.5 - 15

Dimensions US Standard

Usa code	94037209
Ply Rating	8
Section Width (inch)	12.5
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	15.5
Rolling Circumference (inch)	98.7
Rim Rec	10.00 FSDC
ECE	E11-106R-005230
TRA Code	R4

Load capacity (lbs)

mph / psi	48
5	4700

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..