

AW 09 - Technical Specifications



Description

AW 09 has been developed for soil tillage, hay harvesting and transport applications with implements, balers and trailers. It is ideal for modern farming both on and off the road. Its reinforced carcass ensures high load capacity and a longer service tire life. AW 09 has been designed with a special cut-and-chip-resistant compound that provides extraordinary stubble resistance.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Baler, Hay Harvester, Implement Machinery, Trailer

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 260/70 - 15.3 |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Section Width (mm) | 268 |
| Overall Diameter (mm) | 753 |
| Static Loaded Radius (mm) | 335 |
| Rolling Circumference (mm) | 2206 |
| Rim Rec | 9.00 |
| ECE | E4-106R-000374 |

Load capacity (Kg)

| km/h / bar | 5.00 |
|------------|------|
| 10 FR | 2730 |
| 25 FR | 2320 |
| 30 FR | 2185 |
| 40 FR | 1950 |
| 10 DW | 1905 |
| 25 DW | 1620 |
| 30 DW | 1525 |
| 40 DW | 1360 |

Printed on 30/11/2020 08:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..