

AW 09 - Data Sheet



Description

AW 09 has been developed for soil tillage, hay harvesting and transport applications with implements, balers and trailers. It is ideal for modern farming both on and off the road. Its reinforced carcass ensures high load capacity and a longer service tire life. AW 09 has been designed with a special cut-and-chip-resistant compound that provides extraordinary stubble resistance.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Baler, Hay Harvester, Implement Machinery, Trailer

SIZE	Version	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
260/70 - 15.3	STANDARD	9.00		268	753	335	2206	TL	E4-106R-000372
260/70 - 15.3	STANDARD	9.00		268	753	335	2206	TL	E4-106R-000373
260/70 - 15.3	STANDARD	9.00		268	753	335	2206	TL	E4-106R-000374
300/80 - 15.3	STANDARD	9.00		295	860	376	2520	TL	E4-106R-000376
300/80 - 15.3	STANDARD	9.00		295	860	376	2520	TL	E4-106R-000375
300/80 - 15.3	STANDARD	9.00		295	860	376	2520	TL	E4-106R-000377
320/80 - 15.3	STANDARD	9.00		309	901	392	2640	TL	E4-106R-000378
400/60 - 15.5	STANDARD	AG 13.00		404	874	382	2561	TL	E4-106R-000381
380/55 - 17	STANDARD	13.00		390	850	377	2491	TL	E4-106R-000379
380/55 - 17	STANDARD	13.00		390	850	377	2491	TL	E4-106R-000380

Printed on 30/11/2020 09:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..