

## AW 702 - Technical Specifications



### Description

AW 702 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. This heavy-duty tire has been designed by BKT to provide a new level of durability. AW 702 is available in different versions to meet specific end-user needs: an "aramid belted" version is available for those who need strengthened puncture resistance, the "HD" version has a special cut-and-chip resistant compound, while the "special" version provides extraordinary stubble resistance.

### UM

US Standard

### Construction

BIAS

### Machinery

Agriculture: Baler, Implement Machinery, Trailer  
Industrial: Trailer

Version	STANDARD
Type	TT
Tyre Size	14.5/80 - 18

### Dimensions US Standard

Usa code	94034666
Ply Rating	12
Section Width (inch)	14.3
Overall Diameter (inch)	41.2
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	120.8
Rim Rec	11.0
Rim Alt	12; 13
ECE	E11-106R-003601

## Load capacity (lbs)

mph / psi	49
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160

Printed on 26/02/2021 16:23

*All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*