

AW 702 - Data Sheet



Description

AW 702 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. This heavy-duty tire has been designed by BKT to provide a new level of durability. AW 702 is available in different versions to meet specific end-user needs: an "aramid belted" version is available for those who need strengthened puncture resistance, the "HD" version has a special cut-and-chip resistant compound, while the "special" version provides extraordinary stubble resistance.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Baler, Implement Machinery, Trailer
Industrial: Trailer

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.0/80 - 12	ARAMID BELTED	10	9.00	7.0	264	710	313	2080	TL	E11-106R-003576
10.0/80 - 12	SPECIAL	10	9.00	7.0	264	710	313	2080	TL	E11-106R-004353
10.0/80 - 12	STANDARD	10	9.00	7.0	264	710	313	2080	TL	E4-106R-002662
10.0/80 - 12	STANDARD	8	9.00	7.0	264	710	313	2080	TL	
7.00 - 12	ARAMID BELTED	6	4.25		185	665	295	1948	TL	E11-106R-004243
7.00 - 12	STANDARD	6	4.25		185	665	295	1948	TL	E4-106R-001957
10.0/75 - 15.3	HD	18	9.00		274	760	343	2227	TL	E11-106R-005317
10.0/75 - 15.3	SPECIAL	14	9.00		274	760	343	2227	TL	E4-106R-001542
10.0/75 - 15.3	STANDARD	22	9.00		274	760	343	2227	TL	E4-106R-002260
10.0/75 - 15.3	STANDARD	12	9.00		274	760	343	2227	TT	E4-106R-001541
10.0/75 - 15.3	STANDARD	12	9.00		274	760	343	2227	TL	E4-106R-001541
10.0/75 - 15.3	STANDARD	14	9.00		274	760	343	2227	TT	E4-106R-001896
10.0/75 - 15.3	STANDARD	14	9.00		274	760	343	2227	TL	E4-106R-001896
10.0/75 - 15.3	STANDARD	18	9.00		274	760	343	2227	TL	E4-106R-001880
10.0/75 - 15.3	STANDARD	8	9.00		274	760	343	2227	TT	
10.0/75 - 15.3	STANDARD	10	9.00		274	760	343	2227	TT	E4-106R-001540
10.0/75 - 15.3	STANDARD	10	9.00		274	760	343	2227	TL	E4-106R-001540
11.5/80 - 15.3	ARAMID BELTED	14	9.00		297	844	370	2473	TL	E11-106R-004548
11.5/80 - 15.3	STANDARD	18	9.00		297	844	370	2473	TL	E4-106R-001881
11.5/80 - 15.3	STANDARD	10	9.00		297	844	370	2473	TL	E4-106R-001893
11.5/80 - 15.3	STANDARD	12	9.00		297	844	370	2473	TT	E4-106R-001895
11.5/80 - 15.3	STANDARD	12	9.00		297	844	370	2473	TL	E4-106R-001895
11.5/80 - 15.3	STANDARD	14	9.00		297	844	370	2473	TT	E4-106R-001897
11.5/80 - 15.3	STANDARD	14	9.00		297	844	370	2473	TL	E4-106R-001897
11.5/80 - 15.3	STANDARD	16	9.00		297	844	370	2473	TT	E4-106R-002752
11.5/80 - 15.3	STANDARD	18	9.00		297	844	370	2473	TT	E4-106R-001881
11.5/80 - 15.3	STANDARD	10	9.00		297	844	370	2473	TT	E4-106R-001893
11.5/80 - 15.3	STANDARD	16	9.00		297	844	370	2473	TL	E4-106R-002752
12.5/80 - 15.3	SPECIAL	18	9.00		312	885	387	2593	TL	E11-106R-004356
12.5/80 - 15.3	SPECIAL	14	9.00		312	885	387	2593	TT	E11-106R-004354
12.5/80 - 15.3	STANDARD	16	9.00		312	885	387	2593	TT	E11-106R-004355
12.5/80 - 15.3	STANDARD	14	9.00		312	885	387	2593	TL	E11-106R-003602
12.5/80 - 15.3	STANDARD	14	9.00		312	885	387	2593	TT	E11-106R-003602
12.5/80 - 15.3	STANDARD	16	9.00		312	885	387	2593	TL	E11-106R-004355
10.5/65 - 16	INDUSTRIAL	14	W 9	W 8 ; W 8 L	265	760	343	2112	TL	E11-106R-004247
10.5/65 - 16	SPECIAL	10	W 9	W 8 ; W 8 L	265	760	343	2112	TL	E11-106R-004245
10.5/65 - 16	STANDARD	10	W 9	W 8 ; W 8 L	265	760	343	2112	TT	E11-106R-003513

10.5/65 - 16	STANDARD	10	W 9	W 8 ; W 8 L	265	760	343	2112	TL	E11-106R-003513
10.5/65 - 16	STANDARD	14	W 9	W 8 ; W 8 L	265	760	343	2112	TT	E11-106R-004247
10.5/65 - 16	STANDARD	14	W 9	W 8 ; W 8 L	265	760	343	2112	TL	E11-106R-004247
10.50 - 16	STANDARD	14	6.00 T		305	975	445	2986	TT	E11-106R-004244
13.0/55 - 16	STANDARD	12	11.0		336	770	345	2256	TL	E4-106R-001898
13.0/55 - 16	STANDARD	14	11.0		336	770	345	2256	TL	E4-106R-002751
13.0/55 - 16	STANDARD	18	11.0		336	770	345	2256	TL	E4-106R-002332
13.0/75 - 16	STANDARD	10	11.0	9 ; W 9 ; W 11	340	890	396	2726	TL	E4-106R-001899
6.00 - 16	STANDARD	6	4.00 E	4.50 E ; 4½ K	169	722	337	2150	TT	E4-106R-001958
6.00 - 16	STANDARD	6	4.00 E	4.50 E ; 4½ K	169	722	337	2150	TL	E4-106R-001958
6.00 - 16	STANDARD	8	4.00 E	4.50 E ; 4½ K	169	722	337	2150	TT	E11-106R-004357
10.5/80 - 18	STANDARD	10	W 9	W 8 ; 9	275	885	395	2593	TL	E4-106R-002326
10.5/80 - 18	STANDARD	14	W 9	W 8 ; 9	275	885	395	2593	TL	E11-106R-003577
12.5/80 - 18	SPECIAL	14	W 9	11	308	965	432	2827	TL	
12.5/80 - 18	SPECIAL	16	W 9	11	308	965	432	2827	TL	E11-106R-004359
12.5/80 - 18	STANDARD	16	W 9	11	308	965	432	2827	TL	E4-106R-001907
12.5/80 - 18	STANDARD	10	W 9	11	308	965	432	2827	TL	
12.5/80 - 18	STANDARD	12	W 9	11	308	965	432	2827	TL	
12.5/80 - 18	STANDARD	14	W 9	11	308	965	432	2827	TL	E4-106R-001906
12.5/80 - 18	STANDARD	18	W 9	11	308	965	432	2827	TL	E4-106R-001900
13.0/65 - 18	STANDARD	16	11.0		336	890	398	2608	TL	E4-106R-001905
13.0/65 - 18	STANDARD	14	11.0		336	890	398	2608	TT	E11-106R-004248
13.0/65 - 18	STANDARD	14	11.0		336	890	398	2608	TL	
14.5/80 - 18	STANDARD	12	11.0	12 ; 13	362	1047	446	3068	TT	E11-106R-003601

Printed on 26/02/2021 10:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..