# AW 729 - Data Sheet

## Description

AW 729 is an agricultural tire specifically designed for transport, hay harvesting, baling and soil tillage applications. Its rounded shoulder and three central grooves tread design provide low soil compaction and avoids damages to the field.
AW 729 is the ideal tire for modern farming, and it is suited for both on-and-off-the-road usage.

## UM

US Standard

## Construction

BIAS

## Machinery

Agriculture: Baler • Implement Machinery • Trailer

| SIZE | Version | USACode | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **340/55 - 16 (13.0/55 - 16)** | STANDARD | 94066117 | 121 A8 | 133 A8 | | 11.0 | | 13.5 | 30.9 | 14.1 | 92.8 | TL | E11-106R-006421 |
| **15.0/55 - 17** | STANDARD | 94065387 | 122 A8 | 134 A8 | 10 | 13.00 | 13 ; W 13 | 15.2 | 33.5 | 14.8 | 100.8 | TL | E11-106R-006434 |
| **380/55 - 17** | STANDARD | 94074150 | 122 A8 | 134 A8 | 10 | 13.00 | 13 ; W 13 | 15.2 | 33.5 | 14.8 | 100.8 | TL | E11-106R-008727 |
| **480/45 - 17** | STANDARD | 94068975 | 134 A8 | 146 A8 | | 16.00 | | 18.9 | 34.1 | 15.7 | 99.4 | TL | E11-106R-006798 |
| **500/50 - 17** | STANDARD | 94067466 | 137 A8 | 149 A8 | | 16.00 | | 19.7 | 37.2 | 16.8 | 113.6 | TL | E11-106R-006616 |

Printed on 4/25/2024 9:47 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..