BK 823 - Technical Specifications

Description

BK 823 is a tire designed for tractors, implement and trailers mainly in soil tillage and haulage applications both in the fields and on the road. Its special block pattern makes the tire particularly suitable for heavy-duty service where excellent steering performance is required. An HD version is also available with improved cut and chip resistance.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Implement Machinery • Tractor • Trailer

Version	HD
Type	TT
Tyre Size	9.00 - 16
LI/SS	127 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	245
Overall Diameter (mm)	891
Static Loaded Radius (mm)	394
Rolling Circumference (mm)	2583
Rim Rec	6.5
ECE	E11-106R-004338

Load capacity (Kg)

km/h / bar	4.40
40	1750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 9/19/2024 5:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..