



BK-LOADER 53 - Technical Specifications



Description

BK-LOADER 53 is an aramid-belted tire designed for loaders in industrial applications. The unique tread design provides best lateral stability in addition to extended tread wear and extraordinary resistance against cuts and punctures thanks to the extra deep tread. BK-LOADER 53 features outstanding self-cleaning properties as well as excellent grip and traction on both wet and dry surfaces. This tire is particularly suitable for recycling operations.

UM

US Standard

Construction

RADIAL

Machinery

Industrial: Loader

| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 405/70 R 20 |
| LI/SS | 155A2/151A4 |

Dimensions US Standard

| | |
|------------------------------|-------------------------|
| Usa code | 94054428 |
| Section Width (inch) | 16 |
| Overall Diameter (inch) | 43.2 |
| Static Loaded Radius (inch) | 20.1 |
| Rolling Circumference (inch) | 131.5 |
| Rim Rec | 13 |
| Rim Alt | 14 ; 13 SDC; 12 ;12 SDC |

Load capacity (lbs)

| mph / psi | 22 | 29 | 36 | 44 | 51 | 58 | 65 | 73 | 80 |
|-----------|------|------|------|------|------|-------|-------|-------|-------|
| 12 | 2670 | 3350 | 3980 | 4610 | 5240 | 5820 | 6400 | 6990 | 7610 |
| 5 | 3030 | 3800 | 4520 | 5240 | 5950 | 6610 | 7270 | 7940 | 8540 |
| Static | 4850 | 6060 | 7220 | 8380 | 9530 | 10580 | 11680 | 12680 | 13670 |

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..