

CONTAINER KING - Technical Specifications

Description

CONTAINER KING has been designed for reach stackers in intermodal transport and logistics applications. This extraordinary tire is made of a highly wear-and-tear-resistant tread compound which minimizes tread cracks. CONTAINER KING ensures an extended tire life-cycle plus exceptional stability in lift mode.

UM

US Standard

Construction

BIAS

Machinery

- Industrial: Reach Stacker

- Version
INDUSTRIAL
- Type
TL
- Tyre Size
18.00 - 33

Dimensions US Standard

- Usa code
94064526
- Ply Rating
40
- Overall Width (inch)
20.1
- Overall Diameter (inch)
74.6
- Static Loaded Radius (inch)
33.5
- Rolling Circumference (inch)
229.1
- Rim Rec
13.00/2.5
- TRA Code
IND4

Load capacity (lbs)

mph / psi 145

5 59520

Printed on 05/07/2022 15:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..