

EARTHMAX SR 32 - Technical Specifications



Description

EARTHMAX SR 32 is a non-directional wide-base radial tire particularly suitable for scrapers. The tire features a strong All Steel casing and a special tread compound providing excellent cut and puncture resistance as well as durability. Additional traits are exceptional traction and flotation even during heavy-duty operations.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Scraper

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 29
LI/SS	202 B

Dimensions US Standard

Usa code	94066216
TMPH	197
Overall Width (inch)	30.1
Overall Diameter (inch)	78
Static Loaded Radius (inch)	34.8
Rolling Circumference (inch)	236.6
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5
Star Rating	**
TRA Code	E3

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	26800	27600	29100	30000	32000	33100

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..