



FLOTATION RIB 774 - Technical Specifications



Description

FLOTATION RIB 774 is suitable in all free-rolling applications, hay harvesting applications and ideal for trailers. It has been designed to provide best handling comfort optimizing the timing of operations as well as high load capacity and a longer tire life.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Hay Harvester, Trailer

Version	STANDARD
Type	TL
Tyre Size	600/55 - 22.5
LI/SS DRIVE WHEEL	
LI/SS FREE ROLLING	164 A8/160 B

Dimensions US Standard

Usa code	94006625
Ply Rating	12
Section Width (inch)	23.6
Overall Diameter (inch)	48.4
Static Loaded Radius (inch)	21.3
Rolling Circumference (inch)	146.3
Rim Rec	AG 20.00

ECE

Load capacity (lbs)

mph / psi	22	25	29
5 FR	13040	14030	15430
10 FR	11740	12620	13890
20 FR	10430	11220	12350
25 FR	9310	10020	11020
30 FR	8390	9020	9920

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..