

## FLOTATION V LINE - Technical Specifications



### Description

FLOTATION V LINE has been specially designed for trailers in transport applications. It shows high flotation capability and ensures low soil compaction protecting the field. FLOTATION V LINE allows you to carry high loads at low pressure maximizing your business productivity.

### UM

International Standard

### Construction

BIAS

### Machinery

Agriculture: Trailer

|           |               |
|-----------|---------------|
| Version   | STANDARD      |
| Type      | TL            |
| Tyre Size | 550/60 - 22.5 |

### Dimensions International Standard

|                            |          |
|----------------------------|----------|
| Ply Rating                 | 12       |
| Section Width (mm)         | 550      |
| Overall Diameter (mm)      | 1240     |
| Static Loaded Radius (mm)  | 540      |
| Rolling Circumference (mm) | 3725     |
| Rim Rec                    | AG 16.00 |

## Load capacity (Kg)

| km/h / bar | 1.50 | 1.80 | 2.10 |
|------------|------|------|------|
| 10 FR      | 5175 | 5755 | 6300 |
| 20 FR      | 4655 | 5180 | 5670 |
| 30 FR      | 4140 | 4605 | 5040 |
| 40 FR      | 3695 | 4110 | 4500 |
| 50 FR      | 3325 | 3700 | 4000 |
| 10 DW      | 3620 | 4030 | 4410 |
| 20 DW      | 3255 | 3630 | 3970 |
| 30 DW      | 2895 | 3225 | 3530 |
| 40 DW      | 2585 | 2880 | 3150 |
| 50 DW      | 2325 | 2590 | 2800 |

Printed on 05/12/2020 15:46

*All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*