

INDUSTRIAL RIB F3 - Technical Specifications



Description

INDUSTRIAL RIB F3 is an agro-industrial rib-pattern tire designed for field and road transport as well as for soil tillage operations with implement machinery and trailers. This tire features an outstanding stubble-resistant compound making it suitable for the most critical operating conditions and ensuring a long tire life-cycle.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Implement Machinery, Trailer

Version	STANDARD
Type	TL
Tyre Size	11L - 16 SL

Dimensions US Standard

Usa code	94000142
Ply Rating	10
Section Width (inch)	11
Overall Diameter (inch)	32.7
Rim Rec	W 8 L
Rim Alt	8 LB ; 10 LB ; W 10 L
ECE	E11-106R-004304
TRA Code	F3

Load capacity (lbs)

mph / psi	Load Capacity (lbs)
20	2760
25	2470

its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..