



LOADER PLUS - Technical Specifications



Description

LOADER PLUS (L-3) is a bias-ply tire specially designed for loaders. The tread compound provides cut-and-chip-resistant properties and suits best for loading and dozing operations.

UM

US Standard

Construction

BIAS

Machinery

Industrial: Dozer, Loader
OTR: Dozer, Loader

Version	STANDARD
Type	TT
Tyre Size	23.5 - 25

Dimensions US Standard

Usa code	94038046
Ply Rating	20
Overall Width (inch)	23.6
Overall Diameter (inch)	64.6
Static Loaded Radius (inch)	29.5
Rolling Circumference (inch)	191.1
Rim Rec	19.50/2.5
TRA Code	L3

Load capacity (lbs)

mph / psi	
5	24000

Printed on 25/09/2020 19:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..