MP 567 - Technical Specifications

Description

MP 567 is an agro-industrial tire suitable for field and road transport and municipality/maintenance operations. It is the perfect tire for telehandlers and implement machinery. The MP 567 tire provides good traction in all the weather conditions as well as excellent self-cleaning properties. This tire ensures a comfortable driving experience, together with a longer service life.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Implement Machinery • Telehandler
Industrial: Telehandler • Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	16.0/70 - 20 (405/70 - 20)

Dimensions International Standard

Ply Rating	14
Section Width (mm)	405
Overall Diameter (mm)	1128
Static Loaded Radius (mm)	490
Rolling Circumference (mm)	3350
Rim Rec	13 SDC
Rim Alt	12
ECE	E4-54R-0022639

Load capacity (Kg)

km/h / bar	3.50
90	2900
40	3340

Printed on 4/19/2024 5:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..