

MP 590 - Technical Specifications



Description

MP 590 is an agro-industrial tire suitable for loading operations with telehandlers and forklifts. This tire provides good traction and excellent stability as well as increased durability.

UM

US Standard

Construction



Machinery

Agriculture: Telehandler

Industrial: Forklift • Telehandler • Universal Vehicle

Version	STANDARD
Туре	TL
Tyre Size	18 - 22.5 (445/65 - 22.5)

Dimensions US Standard

Usa code	94014729
Ply Rating	16
Section Width (inch)	18.9
Overall Diameter (inch)	46.9
Static Loaded Radius (inch)	20.9
Rolling Circumference (inch)	139.1
Rim Rec	14.0
ECE	E11-106R-003019

Load capacity (lbs)

mph / psi	80
25 DW	10750
20 DW	12010

Printed on 4/19/2024 2:26 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..