MULTIMAX MP 513 - Technical Specifications

Description

MULTIMAX MP 513 has been designed by BKT for multi-purpose vehicles in municipality/maintenance and transport applications, for both agricultural and industrial uses. It is perfect for universal vehicles and fertilizer trucks. Thanks to the strong steel-belted nylon casing, MULTIMAX MP 513 allows to carry heavy loads at high speeds providing a comfortable driving experience. It ensures a longer service life and traction along with outstanding self-cleaning properties.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Universal Vehicle • Fertilizer Truck
Industrial: Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	375/70 R 20 MPT
LI/SS	136 G

Dimensions International Standard

Section Width (mm)	377
Overall Diameter (mm)	1034
Static Loaded Radius (mm)	472
Rolling Circumference (mm)	3121
Rim Rec	12
Rim Alt	W 10 ; DW 10 ; 11 ; 11 SDC ; W 11 ; DW 11 ; 12 SDC
ECE	E11-54R-0016139

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5
90	1210	1435	1705	1975	2240
65	1315	1560	1855	2145	2435
40	1395	1655	1965	2275	2580

Printed on 4/17/2024 5:35 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..