

# POWER TRAX HD SMOOTH - Technical Specifications

## Description

POWER TRAX HD SMOOTH is a bias-ply tire specially designed for port and underground mining operations. The special sidewall protection along with a solid tread prevents cut and puncture damages that are common in such demanding environments. When you need to move heavy-duty loads, Power Trax HD Smooth is your ideal partner.

## UM

### International Standard

### Construction

### BIAS

### Machinery

- Industrial: Container Handler, Forklift
- OTR: Underground Mining Vehicle

- Version  
STANDARD
- Type  
TT
- Tyre Size  
12.00 - 20

### Dimensions International Standard

- Ply Rating  
28
- Section Width (mm)  
320
- Overall Diameter (mm)  
1150
- Rim Rec  
8.50
- Rim Alt  
9.0

### Load capacity (Kg)

	<b>km/h / bar</b>	<b>10.00</b>
25 LOAD WHEEL		9490
25 STEER WHEEL		7300
10 OTHER VEHICLES		9490
25 OTHER VEHICLES		7300
STATIC SIDE LOADER		11025

Printed on 05/07/2022 15:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..