

RIB 774 (A) - Data Sheet



Description

RIB 774 (A) is a low-section implement tire offering high load capacity and a long tire life-cycle. It is suitable for hay harvesting and transport applications with balers and trailers.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Baler, Hay Harvester, Trailer

SIZE	Version	USACode	L/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 8.50 - 8	ARAMID BELTED	94064809	85 A8	6	7.00 I - 55 ; I - 70 ; I - 90		8.9	18.1	8.5	54.7	TL	E11-106R-006268
18 X 8.50 - 8	STANDARD	94056910	85 A8	6	7.00 I - 55 ; I - 70 ; I - 90		8.9	18.1	8.5	54.7	TL	E11-106R-004622
15.0/55 - 17	STANDARD	94010967	141 A8	14	13.00	13	15.4	33.5	14.8	98	TL	E11-106R-004311
15.0/55 - 17	STANDARD	94010936	134 A8	10	13.00	13	15.4	33.5	14.8	98	TL	E11-106R-004309

Printed on 03/12/2021 06:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..