

# SIERRA MAX - Technical Specifications



## Description

SIERRA MAX is the BKT tire for both all-terrain and lawn and garden applications. Its radial construction provides a significantly smoother and more comfortable ride over extreme terrains such as deserts, or dirty and rocky surfaces. The special tread design along with its wider footprint provides outstanding forward and lateral traction.

## UM

International Standard

## Construction

RADIAL

## Machinery

Agriculture: ATV

Version	STANDARD
Type	TL
Tyre Size	AT 27 X 11 R 14
LI/SS	56 N

## Dimensions International Standard

Section Width (mm)	280
Overall Diameter (mm)	700
Static Loaded Radius (mm)	318
Rolling Circumference (mm)	2091
Rim Rec	9.00
Star Rating	***
ECE	E11-75R-005097

## Load capacity (Kg)

km/h / bar	0.50
140	224

*its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*