

## SM 53 - Technical Specifications



### Description

SM 53 has been specially designed for loaders in underground mining and loading applications. It features high stability as well as a smooth tread design providing excellent cut resistance.

### UM

International Standard

### Construction

BIAS

### Machinery

OTR: Underground Mining Vehicle

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20

### Dimensions International Standard

Ply Rating	16
Overall Width (mm)	266
Overall Diameter (mm)	1040
Static Loaded Radius (mm)	472
Rolling Circumference (mm)	3080
Rim Rec	7.0
TRA Code	L35

### Load capacity (Kg)

km/h / bar	
10	3965
15	3450
25	3170

Printed on 05/07/2022 14:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..

