

STEER FARM - Technical Specifications



<i>Description</i>	STEER FARM has been designed for 2WD tractors in soil tillage applications, providing excellent steering performance.
<i>UM</i>	US Standard
<i>Construction</i>	BIAS
<i>Machinery</i>	Agriculture: 2WD Tractor

<i>Version</i>	STANDARD
<i>Type</i>	TT
<i>Tyre Size</i>	7.50 - 16
<i>LI/SS</i>	99 A8

Dimensions US Standard

<i>Usa code</i>	94030859
<i>Ply Rating</i>	8
<i>Section Width (inch)</i>	8.1
<i>Overall Diameter (inch)</i>	31.7
<i>Static Loaded Radius (inch)</i>	14.9
<i>Rolling Circumference (inch)</i>	96.5
<i>Rim Rec</i>	5.50 F
<i>Rim Alt</i>	5.00 F ; 5 K ; 6.00 F
<i>ECE</i>	E11-106R-003547
<i>TRA Code</i>	F2

Load capacity (lbs)

mph / psi	56
25	1710

its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..