

SUPER SAND - Technical Specifications



Description SUPER SAND is particularly suitable for trailers operating on sandy surfaces during hot weather conditions. It features high flotation capability and is ideal for all operations requiring a high level of handling.

UM US Standard

Construction BIAS

Machinery Industrial: Trailer

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 14.00 - 20 |

Dimensions US Standard

| | |
|-------------------------|----------|
| Usa code | 94025763 |
| Ply Rating | 16 |
| Section Width (inch) | 15.2 |
| Overall Diameter (inch) | 48.2 |
| Rim Rec | 10.00 V |
| Rim Alt | 10.00 W |

Load capacity (lbs)

| mph / psi | |
|-----------|------|
| | 70 |
| 40 LS | 7805 |
| 40 LD | 6865 |

Printed on 22/09/2021 07:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..