



SUPER TRAX HD - Technical Specifications



Description

SUPER TRAX HD has been specifically engineered for forklifts in heavy-duty material handling operations, including port and mining applications. The extra deep tread is made of a unique wear-resistant tread compound ensuring a longer service life. SUPER TRAX HD features a strong casing and a reinforced sidewall resulting in both excellent stability and maneuvering in lift mode. The specially designed rim guard provides protection against flats and wheel damage in the rim flange area.

UM

US Standard

Construction

BIAS

Machinery

Industrial: Forklift

| | |
|------------------|-----------|
| <i>Version</i> | STANDARD |
| <i>Type</i> | TT |
| <i>Tyre Size</i> | 7.00 - 12 |

Dimensions US Standard

| | |
|-------------------------------------|----------|
| <i>Usa code</i> | 94053759 |
| <i>Ply Rating</i> | 14 |
| <i>Section Width (inch)</i> | 7.9 |
| <i>Overall Diameter (inch)</i> | 27.2 |
| <i>Static Loaded Radius (inch)</i> | 12.7 |
| <i>Rolling Circumference (inch)</i> | 82.2 |
| <i>Rim Rec</i> | 5.00 S |

Load capacity (lbs)

| mph / psi | 131 |
|--------------------|------|
| 15 LOAD WHEEL | 6075 |
| 15 STEER WHEEL | 4675 |
| 5 OTHER VEHICLES | 6075 |
| 15 OTHER VEHICLES | 4675 |
| STATIC SIDE LOADER | 7055 |

Printed on 05/12/2020 14:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..