

## **TR 173 - Data Sheet**



*Description*

TR 173 is a tractor tire suitable for wet conditions and paddy fields. The special tread pattern provides outstanding self-cleaning properties in addition to reduced soil compaction thanks to a large contact area.

*UM*

International Standard

*Construction*

BIAS

*Machinery*

Agriculture: Tractor

| SIZE      | Version  | LI/SS  | PR | RIM REC | RIM ALT    | SW  | OD   | SLR | RC   | Type | ECE             |
|-----------|----------|--------|----|---------|------------|-----|------|-----|------|------|-----------------|
| 12.4 - 24 | STANDARD | 115 A6 | 6  | W 11    | W 9 ; W 10 | 315 | 1160 | 541 | 3509 | TT   | E11-106R-004480 |
| 13.6 - 26 | STANDARD | 120 A6 | 6  | W 12    | W 11       | 340 | 1255 | 586 | 3786 | TT   | E11-106R-003555 |

Printed on 28/09/2020 18:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..