

TR 319 - Technical Specifications



Description

TR 319 is a tire for implement machinery, orchard harvesters and trenchers in lawn and garden, municipality and soil tillage applications. Featuring a large contact area providing best traction, TR 319 is very suitable for applications on wet surfaces, where stability and self-cleaning properties are required.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Implement Machinery, Orchard Harvester, Trencher

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 29 X 12.50 - 15 |
| LI/SS | 106 B |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94053247 |
| Ply Rating | 8 |
| Section Width (inch) | 12.3 |
| Overall Diameter (inch) | 29.7 |
| Static Loaded Radius (inch) | 14.2 |
| Rolling Circumference (inch) | 89.1 |
| Rim Rec | 10 LB |
| ECE | E11-106R-004605 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 45 |
| 30 | 2090 |

its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..