

TR 319 - Data Sheet



Description

TR 319 is a tire for implement machinery, orchard harvesters and trenchers in lawn and garden, municipality and soil tillage applications. Featuring a large contact area providing best traction, TR 319 is very suitable for applications on wet surfaces, where stability and self-cleaning properties are required.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Implement Machinery, Orchard Harvester, Trencher

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
26 X 12.00 - 12	STANDARD	116 A3	8	10.50 AT	8.0 AT ; 8.5 AT ; 9.0 AT	318	640	290	1908	TL	E11-106R-003560
29 X 12.50 - 15	STANDARD	106 B	8	10 LB		312	755	360	2264	TL	E11-106R-004605
29 X 12.50 - 15	STANDARD	98 B	6	10 LB		312	755	360	2264	TL	E11-106R-004604

Printed on 30/11/2022 11:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..