

TR 387 - Technical Specifications



Description

TR 387 is an agro-industrial tire suitable for sugar cane trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Trailer
Industrial: Compactor

Version	STANDARD
Type	TL
Tyre Size	11.2 - 24
LI/SS	116 A6

Dimensions International Standard

Section Width (mm)	292
Overall Diameter (mm)	1075
Static Loaded Radius (mm)	496
Rolling Circumference (mm)	3228
Rim Rec	W 10
Rim Alt	W 9
ECE	E11-106R-006420
TRA Code	R4

Load capacity (Kg)

km/h / bar

2.40

30

1250

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..