

## TR 387 - Technical Specifications



### Description

TR 387 is an agro-industrial tire suitable for sugar cane trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

### UM

International Standard

### Construction

BIAS

### Machinery

Agriculture: Trailer  
Industrial: Compactor

Version	STANDARD
Type	TL
Tyre Size	18.4 - 26
LI/SS	146 A6

### Dimensions International Standard

Ply Rating	12
Section Width (mm)	475
Overall Diameter (mm)	1430
Static Loaded Radius (mm)	635
Rolling Circumference (mm)	4150
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E4-106R-002718
TRA Code	R3

### Load capacity (Kg)

km/h / bar

30

2.30

3000

*All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*