

TR 387 - Data Sheet



Description

TR 387 is an agro-industrial tire suitable for sugar cane trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Trailer
Industrial: Compactor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
11.2 - 24	STANDARD	R4	116 A6		W 10	W 9	292	1075	496	3228		TL	E11-106R-006420
18.4 - 26	HD	R3	152 A6	16	DW 16 L	DW 15 L	475	1430	635	4150		TL	
18.4 - 26	STANDARD	R3	142 A6	10	DW 16 L	DW 15 L	475	1430	635	4150		TL	E11-106R-004638
18.4 - 26	STANDARD	R3	146 A6	12	DW 16 L	DW 15 L	475	1430	635	4150		TL	E4-106R-002718
23.1 - 26	DUAL BEAD	R3	159 A6	16	DW 20 B		592	1560	690	4688	750	TL	
23.1 - 26	DUAL BEAD HD	R3	161 A6	18	DW 20 B		592	1560	690	4688	750	TT	
23.1 - 26	DUAL BEAD HD	R3	161 A6	18	DW 20 B		592	1560	690	4688	750	TL	
23.1 - 26	HD	R3	164 A6	12	DW 20 B		592	1560	690	4688	750	TL	E11-106R-003647
23.1 - 26	HD DUAL BEAD SPECIAL	R3	161 A6	18	DW 20 B		592	1560	690	4688	750	TL	
23.1 - 26	STANDARD	R3	145 A6	8	DW 20 B		592	1560	690	4688	750	TL	E11-106R-003595
23.1 - 26	STANDARD	R3	153 A6	12	DW 20 B		592	1560	690	4688	750	TL	E4-106R-002317
23.1 - 26	STANDARD	R3	159 A6	16	DW 20 B		592	1560	690	4688	750	TL	E4-106R-002318
12.4 - 28	STANDARD	R3	123 A6	8	W 11	W 9 ; W 10	325	1200	550	3576		TL	E11-106R-005277
16.9 - 28	STANDARD	R3	135 A6	8	DW 15 L	DW 14 L	440	1400	630	4074		TL	E11-106R-005278
16.9 - 30 (14 - 30)	STANDARD	R3	137 A6	8	DW 15 L	DW 14 L	440	1450	655	4220		TL	E11-106R-005279
18.4 - 30 (15 - 30)	HD	R3	151 A6	14	DW 16 L	DW 15 L	475	1530	680	4395		TT	
18.4 - 30 (15 - 30)	STANDARD	R3	139 A6	8	DW 16 L	DW 15 L	475	1530	680	4395		TL	
620/75 - 30 (23.1 - 30)	DUAL BEAD	R3	161 A6	16	DW 20 A ; DW 20 B		605	1675				TL	
620/75 - 30 (23.1 - 30)	DUAL BEAD HD	R3	164 A6	18	DW 20 A ; DW 20 B		605	1675	0	0		TL	
24.5 - 32	DUAL BEAD HD	R3	164 A6	16	DH 21	DH 21 B ; DH 21 H ; DH 21 HB	625	1755	790	5226		TL	

Printed on 26/11/2022 16:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..