

## **TR 387 - Data Sheet**



*Description*

TR 387 is an agro-industrial tire suitable for sugar cane trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

*UM*

US Standard

*Construction*

BIAS

*Machinery*

Agriculture: Trailer  
Industrial: Compactor

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE	
11.2 - 24	STANDARD	94066124	R4	112 A8		W 10	W 9	11.5	42.3	19.5	127.1	TL	E11-106R-006420	
18.4 - 26	HD	94034086	R3	148 A8	16	DW 16 L	DW 15 L	18.7	56.3	25	163.4	TL		
18.4 - 26	STANDARD	94004980	R3	138 A8	10	DW 16 L	DW 15 L	18.7	56.3	25	163.4	TL	E11-106R-004638	
18.4 - 26	STANDARD	94005000	R3	142 A8	12	DW 16 L	DW 15 L	18.7	56.3	25	163.4	TL	E4-106R-002718	
23.1 - 26	DUAL BEAD	94005130	R3	155 A8	16	DW 20 B		23.3	61.4	27.2	184.4	TL	E11-106R-003647	
23.1 - 26	DUAL BEAD HD	94027767	R3	157 A8	18	DW 20 B		23.3	61.4	27.2	184.4	TT		
23.1 - 26	DUAL BEAD HD	94030682	R3	157 A8	18	DW 20 B		23.3	61.4	27.2	184.4	TL		
23.1 - 26	HD	94005154	R3	162 A8	12	DW 20 B		23.3	61.4	27.2	184.4	TL		
23.1 - 26	HD DUAL BEAD SPECIAL	94030941	R3	157 A8	18	DW 20 B		23.3	61.4	27.2	184.4	TL		
23.1 - 26	STANDARD	94005048	R3	141 A8	8	DW 20 B		23.3	61.4	27.2	184.4	TL		E11-106R-003595
23.1 - 26	STANDARD	94005079	R3	149 A8	12	DW 20 B		23.3	61.4	27.2	184.4	TL		E4-106R-002317
23.1 - 26	STANDARD	94005116	R3	155 A8	16	DW 20 B		23.3	61.4	27.2	184.4	TL		E4-106R-002318
12.4 - 28	STANDARD	94004959	R3	120 A8	8	W 11	W 9 ; W 10	12.8	47.2	21.7	140.8	TL		
16.9 - 28	STANDARD	94004966	R3	131 A8	8	DW 15 L	DW 14 L	17.3	55.1	24.8	160.4	TL		
16.9 - 30 (14 - 30)	STANDARD	94004973	R3	132 A8	8	DW 15 L	DW 14 L	17.3	57.1	25.8	166.1	TL		
18.4 - 30 (15 - 30)	HD	94005147	R3	147 A8	14	DW 16 L	DW 15 L	18.7	60.2	26.8	173	TT		
18.4 - 30 (15 - 30)	STANDARD	94005024	R3	135 A8	8	DW 16 L	DW 15 L	18.7	60.2	26.8	173	TL		
620/75 - 30 (23.1 - 30)	DUAL BEAD	94063956	R3	157 A8	16	DW 20 A ; DW 20 B		23.8	65.9	0	0	TL		

620/75 - 30 (23.1 - 30)	DUAL BEAD HD	94052868	R3	160 A8	18	DW 20 A ; DW 20 B		23.8	65.9	0	0	TL	
24.5 - 32	DUAL BEAD HD	94048854	R3	160 A8	16	DH 21	DH 21 B ; DH 21 H ; DH 21 HB	24.6	69.1	31.1	205.7	TL	

Printed on 28/02/2021 07:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..