

# TR 459 - Technical Specifications



**Description**

TR 459 has been particularly designed for digging and loading operations as well as municipality and maintenance applications with tractors and backhoe loaders. It offers high stability and is available in two versions. The "special" version provides an extended tire life-cycle.

**UM**

US Standard

**Construction**

BIAS

**Machinery**

Agriculture: Backhoe Loader, Tractor  
Industrial: Backhoe Loader

|           |            |
|-----------|------------|
| Version   | INDUSTRIAL |
| Type      | TL         |
| Tyre Size | 21L - 28   |
| LI/SS     | 157 A8     |

### Dimensions US Standard

|                         |                 |
|-------------------------|-----------------|
| Usa code                | 94044337        |
| Ply Rating              | 12              |
| Section Width (inch)    | 21.1            |
| Overall Diameter (inch) | 58.3            |
| Rim Rec                 | DW 18 A         |
| ECE                     | E11-106R-005335 |
| TRA Code                | R4              |

### Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 32   |
| 25        | 9100 |

*its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*