

AGRI TRAILER - Technical Specifications



Description

AGRI TRAILER has been specially designed for tractor trailers. It is the ideal tire for modern farming, suitable for transport applications both on and off the road. Its robust construction results in high load capacity, whereas its extradeep tread allows for a better mileage and a longer service life

UM

US Standard

Construction



Machinery

Agriculture: Trailer

Version	STANDARD
Туре	ΤΤ
Tyre Size	10.00 - 20

Dimensions US Standard

Usa code	94050352
Ply Rating	18
Section Width (inch)	11.3
Overall Diameter (inch)	42.5
Rim Rec	7.5
Rim Alt	7.0;8.0

Load capacity (lbs)

mph / psi	-	-
	-	-
	_	_

Printed on 4/19/2024 10:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..