

AGRIMAX ELOS - Technical Specifications



Description

AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	480/80 R 38 (18.4 R 38)
LI/SS	149 A8/B

Dimensions US Standard

Usa code	94053766
Section Width (inch)	19.3
Overall Diameter (inch)	71
Static Loaded Radius (inch)	32.3
Rolling Circumference (inch)	210.9
Rim Rec	W 16 L
Rim Alt	W 15 L ; DW 16 L
ECE	E11-106R-002991
TRA Code	R2

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	3950	4590	5240	5870	6530	7160
25	3950	4590	5240	5870	6530	7160
20	4220	4920	5610	6290	6990	7670
5 LT	5290	6150	7010	7880	8740	9600
5 HT	4220	4920	5610	6290	6990	7670

Printed on 4/29/2024 12:17 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..