

AGRIMAX ELOS - Technical Specifications



Description

AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	520/85 R 46
LI/SS	169 A8/169 B

Dimensions US Standard

Usa code	94070503
Section Width (inch)	20.9
Overall Diameter (inch)	81.7
Static Loaded Radius (inch)	37.7
Rolling Circumference (inch)	247.8
Rim Rec	DW 16 L
Rim Alt	DW 15 L ;DW 18 L; W 15 L ; W 16 L; W18 L; DD 16 L ; DD 18 L
ECE	E11-106R-007935
TRA Code	R2

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46
30	4990	5890	6780	7550	8440	9210	10110	11130	12030	12790
25	4990	5890	6780	7550	8440	9210	10110	11130	12030	12790
20	5350	6300	7260	8080	9040	9870	10820	11920	12870	13690
5 LT	6690	7890	9090	10120	11320	12350	13550	14910	16110	17140
5 HT	5350	6300	7260	8080	9040	9870	10820	11920	12870	13690

Printed on 12/10/2023 11:32 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..