

# AGRIMAX FORCE - Technical Specifications



## Description

AGRIMAX FORCE, the high-end product of BKT, is a radial tire specially designed for soil tillage, haulage and harvesting applications with high-power tractors and harvesters, ensuring top performance and efficiency. Thanks to its IF technology, this tire can carry heavy loads with a lower inflating pressure compared to a standard tire reducing soil compaction. AGRIMAX FORCE features a reinforced bead and provides enhanced traction, top self-cleaning properties and fuel economy in addition to a comfortable riding experience.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Harvester • High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	IF 650/65 R 34 CFO
LI/SS	161 D

## Dimensions US Standard

Usa code	94040742
Section Width (inch)	25.6
Overall Diameter (inch)	67.3
Static Loaded Radius (inch)	30.1
Rolling Circumference (inch)	199.9
Rim Rec	DW 23 B
Rim Alt	DW 20 B
ECE	E4-106R-001826
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
45	5190	6120	6940	7790	8530	9270
From 40 to 25	5710	6720	7640	8560	9380	10200
20	5930	6990	7940	8910	9750	10600
12	6160	7250	8240	9250	10130	11010
5	7240	8530	9700	10870	11900	12940
Upto 20 Cyc	7420	8740	9920	11130	12190	13250
Upto 10 Cyc	8840	10420	11840	13270	14540	15800
5HT	5930	6990	7940	8910	9750	10600

Printed on 12/8/2023 11:30 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..