



AGRIMAX FORTIS - Data Sheet



Description

AGRIMAX FORTIS is your reliable partner for all preparation, soil tillage and haulage operations. Designed to equip the latest, most modern and most powerful tractors, AGRIMAX FORTIS allows you to carry very high loads reaching up to 65 km/h (40 MPH). It ensures outstanding traction along with top handling and best comfort for a perfect driving experience. The tire has been designed with a reinforced nylon casing for enhanced productivity in the fields preserving the soil thanks to reduced compaction.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Sprayer

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
600/70 R 30	SPECIAL	94058914	R1W	158 D/161 A8	DW 20 B	DW 18 L ; W 18 L	24.1	63.1	28.5	189.4	TL	E4-106R-001400
600/70 R 30	STANDARD	94032952	R1W	158 D/161 A8	DW 20 B	DW 18 L ; W 18 L	24.1	63.1	28.5	189.4	TL	E4-106R-001400
600/70 R 34	SPECIAL	94050116	R1W	160 D/163 A8	DW 18 L	DW 20 B ; W 18 L	23.3	67.1	30	201.1	TL	E4-106R-001401
600/70 R 34	STANDARD	94035649	R1W	160 D/163 A8	DW 18 L	DW 20 B ; W 18 L	23.3	67.1	30	201.1	TL	E4-106R-001401
650/85 R 38	SPECIAL	94058907	R1W	173 D/176 A8	DW 23 B	DW 21 B ; DW 20 B	26.6	81.5	36.8	243.5	TL	E4-106R-001426
650/85 R 38	STANDARD	94029730	R1W	173 D/176 A8	DW 23 B	DW 21 B ; DW 20 B	26.6	81.5	36.8	243.5	TL	E4-106R-001426
800/70 R 38	STANDARD	94032969	R1W	178 D/181 A8	DW 25 B	DW 27 B	31.4	82.1	35.9	244.2	TL	E4-106R-001424
710/75 R 42	SPECIAL	94050123	R1W	175 D/172 E	DW 23 B	DW 25 B	28.2	84	38.2	252.2	TL	E4-106R-001835
710/75 R 42	STANDARD	94034710	R1W	175 D/172 E	DW 23 B	DW 25 B	28.2	84	38.2	252.2	TL	E4-106R-001835

Printed on 5/3/2024 2:31 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..