

AGRIMAX RT 600 - Technical Specifications

Description

AGRIMAX RT 600 is the ideal tire for grassland, harvesting and spreading applications. Thanks to its large contact area, AGRIMAX RT 600 ensures an excellent pressure distribution on the land reducing damage on grassland and protecting your soil. Thanks to its round shoulder technology, the reinforced bead and increased number of lugs, it guarantees great stability and traction.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Harvester • Spreader • Tractor



Version	STANDARD
Type	TL
Tyre Size	800/65 R 32 (30.5L R 32)
LI/SS	176 A8/173 B

Dimensions US Standard

Usa code	94044795
Section Width (inch)	30.5
Overall Diameter (inch)	71.7
Static Loaded Radius (inch)	32.4
Rolling Circumference (inch)	218.8
Rim Rec	DW 27 B
Rim Alt	DH 27 B ; DW 25 B
ECE	E4-106R-001428

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	44	46	52
30	7000	8070	9890	10800	11870	12930	14000	14330	-	-
25	7610	8760	10750	11740	12900	14050	15210	15650	-	-
20	8150	9380	11510	12570	13800	15050	16280	16750	-	-
5 LT	10200	11750	14410	15740	17280	18840	20390	20980	-	-
5 HT	8150	9380	11510	12570	13800	15050	16280	16750	-	-
5 Cyc.	-	12470	15940	17550	20390	22350	24370	25440	26510	27420

Printed on 4/26/2024 11:24 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..