

## AGRIMAX RT 657 - Technical Specifications



### Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor • Vineyard Harvester

|           |              |
|-----------|--------------|
| Version   | STANDARD     |
| Type      | TL           |
| Tyre Size | 540/65 R 30  |
| LI/SS     | 150 D/153 A8 |

## Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Section Width (mm)         | 530            |
| Overall Diameter (mm)      | 1464           |
| Static Loaded Radius (mm)  | 670            |
| Rolling Circumference (mm) | 4403           |
| SRI (mm)                   | 700            |
| Rim Rec                    | W 16 L         |
| Rim Alt                    | W 18 L         |
| ECE                        | E4-106R-000651 |
| TRA Code                   | R1W            |

## Load capacity (Kg)

| km/h / bar | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 65         | 1610 | 1880 | 2115 | 2345 | 2580 | 2785 | 3085 | 3350 |
| 50         | 1690 | 1975 | 2220 | 2465 | 2715 | 2925 | 3240 | 3520 |
| 40         | 1755 | 2045 | 2300 | 2555 | 2815 | 3030 | 3360 | 3650 |
| 30         | 1855 | 2160 | 2430 | 2700 | 2970 | 3200 | 3550 | 3855 |
| 10 LT      | 2160 | 2515 | 2830 | 3145 | 3460 | 3730 | 4135 | 4490 |
| 10 HT      | 1855 | 2160 | 2430 | 2700 | 2970 | 3200 | 3550 | 3855 |

Printed on 3/3/2024 4:45 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..