

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	650/65 R 38
LI/SS	178 A8/175 B

Dimensions US Standard

Usa code	94074853
Section Width (inch)	25.4
Overall Diameter (inch)	71.5
Static Loaded Radius (inch)	32.6
Rolling Circumference (inch)	216.1
Rim Rec	DW 20 B
Rim Alt	DW 21 B ; DW 23 B
ECE	E11-106R-008886
TRA Code	R1W

Load capacity (lbs)

	mph / psi	51
	30	15190
	25	16540
	20	17710
	15	18370
	5	24810
	Static	38030
	5 LT	23150
	12 LT	19850
	5 HT	17710

Printed on 5/2/2024 12:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..