

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	650/65 R 42
LI/SS	165 D/168 A8

Dimensions US Standard

Usa code	94029501
Section Width (inch)	25.4
Overall Diameter (inch)	75.3
Static Loaded Radius (inch)	34.6
Rolling Circumference (inch)	228.7
Rim Rec	DW 20 B
Rim Alt	DW 21 B ; DW 23 B
ECE	E4-106R-000625
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	5460	6360	7150	7950	8750	9420	10450	11400
30	5730	6680	7520	8360	9190	9910	10980	11930
25	5930	6920	7780	8640	9510	10250	11360	12350
20	6270	7320	8230	9150	10060	10850	12030	13060
5 LT	7310	8530	9600	10660	11730	12640	14010	15220
5 HT	6270	7320	8230	9150	10060	10850	12030	13060

Printed on 5/2/2024 12:36 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..