

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	220/70 R 16
LI/SS	99 A8/B

Dimensions International Standard

Section Width (mm)	221
Overall Diameter (mm)	715
Static Loaded Radius (mm)	324
Rolling Circumference (mm)	2145
SRI (mm)	340
Rim Rec	W 7
Rim Alt	W 8
ECE	E11-106R-003354
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	365	420	485	545	605	670	725	775
40	365	420	485	545	605	670	725	775
30	395	450	515	585	650	715	775	830
10 LT	490	656	645	730	815	895	970	1040
10 HT	395	450	515	585	650	715	775	830

Printed on 4/28/2024 2:08 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..