

# AGRIMAX RT 855 - Technical Specifications



## Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	IMPLEMENT
Type	TL
Tyre Size	210/95 R 16 (7.50 R 16)
LI/SS	116A8
LI/SS FREE ROLLING	116 A8

## Dimensions US Standard

Usa code	94069965
Section Width (inch)	8.4
Overall Diameter (inch)	31.7
Static Loaded Radius (inch)	13.8
Rolling Circumference (inch)	92.6
Rim Rec	W 7
Rim Alt	W 6 ; 6 LB
ECE	E11-106R-006625
TRA Code	R1W

## Load capacity (lbs)

mph / psi	35
25 Free Rolling	2760

Printed on 4/28/2024 10:37 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..